


## FIXED EDGE

THICKNESS	1-3/4" - 2-1/4" (± 1/16")		
MAXIMUM SIZE	Singles	Level 1-3 4' x 10'	Level 4-8 4' x 9'
	Pairs	8' x 10'	8' x 9'
	DE Pairs	8' x 10'	8' x 9'
		<i>For oversized doors please consult VT</i>	
CORE	Bullet Resistant		
VERTICAL EDGES (STILES)	Maple with matching fixed vinyl edge		
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	Structural Composite Lumber (SCL) - sealed top & bottom rails		
FACES	Inpro Rigid Vinyl		
CROSSBANDS	High Density Fiberboard (HDF), 20% of door construction weight, pre-consumer recycled material		
STANDARD BEVEL	1/8" in 2" or 3°		
FINISH	Woodgrains, solid colors, & elements		
ADHESIVE	Type 1 adhesive		
FACTORY MACHINING	Pre-drilled hinge pilot holes; all cutouts for mortise hardware should be made at the factory from hardware manufacturer's templates & approved shop drawings		
ACOUSTICAL RATING	Refer to STC chart and STC cut sheets		
QUALITY STANDARDS	WDMA I.S. 1-A & AWS Section 9 Quality Standards (Bonded Core)		
WDMA PERFORMANCE LEVEL	Heavy duty; For extra heavy duty, blocking is required		
SUSTAINABILITY	<ul style="list-style-type: none"> <li>• CARB Phase 2 / TSCA VI Compliant</li> <li>• GREENGUARD GOLD or SCS Advantage Gold</li> <li>• FSC upon request, Consult VT for LEED documentation</li> <li>• Environmental Product Declaration (EPD)</li> <li>• Health Product Declaration (HPD)</li> </ul>		
DOOR WEIGHT	Weight varies depending on level		
WARRANTY	Limited Lifetime, Interior use only. <a href="#">View warranty</a>		



Palladium BR-5, Fixed Edge

### ADDITIONAL DOOR FEATURES & STANDARDS

**CUTOUTS:** 5" minimum distance from door edge & the minimum distance between lite & lock cut out is 1-1/2"

**CLEARANCES:** 1/8" top, 1/8" lock & hinge stiles. See NFPA-80 6.3.1.7.1. Bottom clearance 3/4" max (bottom of the door to top finish floor) See NFPA-80 4.8.4.1

**SECURITY RATING:** Class 40, ASTM 476 (highest rating possible)

**LABELING:** Positive pressure, Category A 20-minute Intertek/Warnock Hersey fire labels shall be available within size & usage approvals.

Fire-rated doors must use approved lite frames. UL 10C

**PACKAGING:** Doors shall be individually poly-bagged for protection & marked as per tag openings on shop drawings

**ACCESSORIES:** Door bottoms, sweeps, thresholds, gasketing, lite kits & glass may be supplied by VT or others

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.