



5-PLY BONDED PARTICLEBOARD CORE (PC), STRUCTURAL COMPOSITE LUMBER CORE (SCLC) AGRIFIBER (WSPC) OR FIRE COMPOSITE; NON-RATED & 20-90-MINUTE POSITIVE PRESSURE

WOOD VENEER, HPDL, OR MDO

THICKNESS	1-3/4" - 2-1/4" (± 1/16")
MAXIMUM SIZE	Non-rated singles: 4'-0" x 10'-0". Singles / Pairs: 20-90-Min, please consult fire capability chart for size restrictions <i>For oversized doors please consult VT</i>
CORE	Particleboard, Structural Composite Lumber, Agrifiber, or Fire Composite (Pyroforce)
VERTICAL EDGES (STILES)	Structural Composite Lumber (SCL), with matching/compatible wood/veneer or finished mill option.
HORIZONTAL EDGES (TOP & BOTTOM RAILS)	Structural Composite Lumber - sealed top & bottom rails
FACES	Wood veneer, HPDL Horizontal Grade Standard (HGS) meets NEMA standard LD-3, MDO
CROSSBANDS	High Density Fiberboard (HDF), 20% of door construction weight, Pre-consumer recycled material
METAL INLAYS	Reveal widths of 1/4"-3/4" wide, straight lines only; flush with door face
STANDARD BEVEL	1/8" in 2" or 3°
FINISH	Wood veneer: WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane); Primed factory finish or opaque finish; laminate: woodgrains, solid colors, & patterns
VENEER MATCH / FACE ASSEMBLY	Book match standard. Slip or random available; face assembly: running match standard, center, balanced, or center balanced available
ADHESIVE	Type 1 adhesive
FACTORY MACHINING	Pre-drilled hinge pilot holes. all cutouts for mortise hardware should be made at the factory from hardware manufacturer's templates & approved shop drawings
QUALITY STANDARDS	WDMA I.S. 1-A & AWS, Section 9 Quality Standards (Bonded Core)
WDMA PERFORMANCE LEVEL	Extra heavy duty
SUSTAINABILITY	<ul style="list-style-type: none"> • CARB Phase 2 / TSCA VI Compliant • GREENGUARD GOLD or SCS Indoor Advantage Gold • FSC upon request, Consult VT for LEED documentation • Environmental Product Declaration (EPD) • Health Product Declaration (HPD)
DOOR WEIGHT	Please consult VT
WARRANTY	Limited Lifetime, Interior use only. View warranty



ADDITIONAL DOOR FEATURES

PAIRS & SETS: Pair match standard, set match available

DOORS/TRANSOMS: Continuous match standard. End or no match available

CUTOUTS: 6" minimum distance from door edge & the minimum distance between lite & lock cut out is 3-5/16"

CLEARANCES: 1/8" top, 1/8" lock & hinge stiles. See NFPA-80 6.3.1.7.1. Bottom clearance 3/4" max (bottom of the door to top finish floor) See NFPA-80 4.8.4.1

SECURITY RATING: Class 40, ASTM 476 (highest rating possible)

PACKAGING: Doors shall be individually poly-bagged by request for protection & marked as per tag openings on shop drawings

ACCESSORIES: Door bottoms, sweeps, thresholds, gasketing, lite kits & glass may be supplied by VT or others

VT INDUSTRIES RESERVES THE RIGHT TO CHANGE DESIGN AND/OR DETAILS OF ITS PRODUCTS WITHOUT NOTICE.